



TRANSCUBE *Container Static*

Static fuel tank container, 110% bunded, pump cabinet c/w equipment storage area, built to BS799 Part 5 & complies with PPG2 Regulations

- 🔴 110% bunded fuel storage container to comply with PPG2 (Pollution Prevention Guidelines) UK Regulations.
- 🔴 CSC plated - made to Convention for Safe Container Standard.
- 🔴 Corner twist locks top and bottom for ease of handling.
- 🔴 Can be stacked 6 high full of fuel, reducing storage space requirements and when on location.
- 🔴 Pump, valves, outlets and fittings are all housed within the lockable cabinet which is fitted with a spill catchment sump.
- 🔴 Outlets are all top mounted to help prevent fuel leakage with optional bottom Outlets.
- 🔴 For additional security, hoses can be fed through any of the 4 letterboxes enabling doors to be kept locked whilst in use.
- 🔴 Quality contents and bund gauges.
- 🔴 Fast fill fuel connection in cabinet with optional overfill prevention device.
- 🔴 Access ladder to operating platform for top filling and maintenance operations on both sides with kick plates
- 🔴 Inner tank can be accessed via manholes for maintenance and inspection.
- 🔴 Option for up to 4 sets of feed & return connections plus pump/auxiliary equipment feed.
- 🔴 Marine specification paint and application Ral 9001 White

Specification

Standard Tank Fittings: 3" offset fill: 3" suction: 1 x 1 1/2" Pump Feed: 4 sets x 1" Feed & Return Pipes: Tank Dip stick: Battery Bund Alarm: 2 x bolted top manholes: Tank Vent open to bund: 2" vent pipe. No Overfill Valve fitted.	
Capacity (brim full) Litres: 27,000 (6000 IMPG) (7100 USG)	Inner Tank: 6mm (S235)
Safe Fill Litres (Nominal Capacity 95%): 25,650 (5765 IMPG) (6785 USG)	Bund: 4mm (S235)
Dimensions (mm) L x W x H: 6058 x 2438 x 2896 (20'x 8' x 9'5")	Environmental standard: COP Regulations (PPG2)
Weight Empty (Approx. Kg): 9740 (21428 lbs)	Design Approval (Frame): ISO 668:1995 CSC plated
Weight Full (Approx. Kg): 32420 (71320 lbs)	Design Standard: COP Regulations (PPG2) BS799 part 5 Type J, Test pressure 6.3 psi (45KPA)
Cabinet Size approx. (mm): W=2150 / D=750 / H=1150	
Tank designed to contain: Diesel/Lubricants	

Energia Model Trading & General Contracting Co. Ltd.

C.R. 2055013666

P.O. Box 30305 Al-Jubail 31951 - Kingdom of Saudi Arabia
Tel.: +966-13-363 5476 / 363 5477 - Fax: +966-13-363 5576
E-mail: info@energiaksa.com - web: www.energiaksa.com
Paid up Capital S.R. 1000,000

شركة الطاقة النموذجية للتجارة والمقاولات العامة
(ذات مسؤولية محدودة) ٢٠٥٥٠١٣٦٦٦

ص ب ٣٠٣٠٥ - الجبيل ٣١٩٥١ - المملكة العربية السعودية
تلفون: ٥٤٧٦ ٣٦٣ / ٥٤٧٧ ٣٦٣ - فاكس: ٥٥٧٦ ٣٦٣ - ١٣-٩٦٦
بريد إلكتروني: info@energiaksa.com - www.energiaksa.com
رأس المال المدفوع ريال سعودي: ١,٠٠٠,٠٠٠